

EMIRATES ATF – D VI & T IV

(Full Synthetic ATF)

DESCRIPTION

EMIRATES 1 DEXRON®-VI / MERCON® LV Full Synthetic Automatic Transmission Fluid is a high performance fluid formulated specifically to meet and exceed **GM DEXRON®-VI and Ford MERCON® LV** specifications. Specially blended using premium synthetic base oils and state-of-the-art additive technology ensures peak performance and maximum fuel economy while meeting the frictional and wear requirements of these advanced automatic transmission fluid specifications.

EMIRATES 1 ATF T IV is universal ATF for the latest generation of automatic transmission formulated from hydro cracking oils and PAO with special additives and inhibition to ensure the proper operation of the automatic transmission.

APPLICATIONS

EMIRATES 1 ATF DEXRON®-VI / MERCON® LV is designed to replace and supersede previous generation specifications from GM and Ford such as DEXRON III and MERCON V.

EMIRATES 1 ATF T IV is developed for use in automatic transmission, especially for Toyota and Aisin AW. **EMIRATES 1 ATF T IV** Fluid can replace T, T-II and T-III Fluids.

Other transmission fluid applications met with this advanced technology include (but not limited to) low viscosity fluid specifications listed by: **Aisin Warner, Allison ,Audi, BMW, Chrysler, Fiat, Honda/Acura, Isuzu ,Jaguar ,JASO ,MAN, Mazda, Mercedes Benz, Mitsubishi, Nissan/Infiniti, Porsche, Peugeot, Saab ,Saturn, Subaru, Suzuki ,Toyota/Lexus/Scion ,Voith, Volvo, Volkswagen & ZF.**

PRODUCT BENEFITS

- Advanced additive chemistry – smooth, consistent shift performance
- Compatibility – ideal for top-up or complete replacement for OEM fluids
- Reduces sludge and varnish build-up
- Outstanding low temperature performance
- Anti-wear protection
- Extended service life
- Improved anti-wear protection which contributes to extended transmission life

Recommendations / Specifications

EMIRATES 1 DEXRON®-VI / MERCON® LV Meets or Exceeds the requirements of **General Motors DEXRON®-VI, Ford MERCON® LV, newer GM vehicles, MB 236.41, Allison C-4 & VOITH H55.6335xx.**

EMIRATES 1 ATF T IV Meets or Exceeds **Toyota and Aisin AW, BMW, OPEL/GM, Land Rover, RENAULT, TOYOTA, VOLVO, VW/AUDI, NISSAN, Mazda, ESSO, Land Rover & Fiat.**

TYPICAL TECHNICAL PROPERTIES

Product	D VI	T IV
Color, VISUAL	RED	RED
Density at 15°C, g/ml, ASTM D4052	0.850	0.852
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	29.0	33
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	6.2	6.9
Viscosity Index, ASTM D2270	172	180
Flash Point(COC), °C, ASTM D92	220	208
Pour Point, °C, ASTM D97	-51	-48
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	10,000	12,000

*C & B: Clear & Bright

Note: The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional queries, please contact Emirates 1 Technical Service Department.

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS). Safety Data Sheets available on request.

Available in: **Cartons:** 12x 1 L, 24x1 L, 4x5L 6 x 4 L, 6 x 5 L, **Pails:** 20 L & 25 L., **Drums:** 200 L, 208 L